



Glacier (POU Water Cooler)

The Glacier Point-of-Use water dispenser is available in Hot & Cold models. The rounded cabinet and fluted front give the Glacier a classic Greek column design suitable for any environment. While being aesthetically pleasing, the polyethylene cabinet's smooth finish is easily cleaned and refurbished. This commercial grade cooler will deliver years of trouble free optimum performance.

Glacier: Hot & Cold



Child-proof
hot water faucet



Removable drip tray



Hot water ON
and OFF switch

Specifications:

| ITEM | | SPECIFICATIONS |
|--------------------------|--------------|--------------------------------|
| Power rating | | Single phase |
| | | 100V-115V 60Hz |
| Standard current | | H&C: 6.2A |
| Power Consumption | Cold | 74W |
| | Hot | 450W |
| Cold | Compressor | Single phase motor (TS24 LATG) |
| | Refrigerant | R134a |
| | Capacity | 3.5L (0.9 gal) |
| Hot | Heater | Band heater |
| | Temp range | 75-92°C (167-197.6°F) |
| | Temp control | 82-89°C (179.6-192.2°F) |
| | Capacity | 4.5L (1.2 gal) |
| Refrigerant charge | | 28.4g (1.0 oz) |
| Product weight | | H&C: 14.7kg (32.4 lb) |
| Product boxed weight | | H&C: 15.8kg (34.8 lb) |
| Product dimensions | | 312(W) X 314 (D) X 980(H)mm |
| | | 12.2"(W) X 12.4"(D) X 38.6"(H) |
| Product boxed dimensions | | 330(W) X 320(D) X 1000(H)mm |
| | | 12.6"(W) X 13.0"(D) X 39.4"(H) |
| Loading quantity | | 20' Container: 238 Units |
| | | 40' Container: 476 Units |
| Certifications | | C-UL-US, CE, CB, CCC, SASO |

This Company has a policy of continuous development and reserves the right to change specifications without notification. For further clarifications, please contact us at cmsales@crystalcoolers.com